

09/831488

JG17 Rec'd PCT/PTO 09 MAY 2001

Attorney Docket No. SWIN 2241
Express Mail
Label No: ET213589025
Date of Deposit: May 9, 2001

CHAPTER II

TRANSMITTAL LETTER TO THE UNITED STATES ELECTED OFFICE (EO/US)

(ENTRY INTO U.S. NATIONAL PHASE UNDER CHAPTER II)

<u>PCT/GB99/03785</u>	<u>12 November 1999 (12.11.99)</u>	<u>14 November 1998 (14.11.98)</u>
INTERNATIONAL APPLICATION NO.	INTERNATIONAL FILING DATE	PRIORITY DATE CLAIMED

ACTUATOR APPARATUS

TITLE OF INVENTION

David COLEY (West Midlands, United Kingdom)

APPLICANT(S)

**Assistant Commissioner for Patents
Box PCT
Washington, D.C. 20231**

Attention: EO/US

1. Applicant herewith submits to the United States Elected Office (EO/US) the following items under 35 USC 371:
 - A. ☒ This express request to immediately begin national examination procedures (35 USC 371(f)).
 - B. ☒ The U.S. National Fee (35 USC 371(c)(1) and other fees (37 CFR 1.492) indicated in the attached fee calculation sheet.

2. ☒ A copy of the International application as filed [35 USC 371(c)(2)]:
 - a. ☐ is transmitted herewith.
 - b. ☐ is not required as the application was filed with the United States Receiving Office.
 - c. ☒ has been transmitted
 - i. ☒ by the International Bureau. Date of mailing of the application (from form PCT/IB/308): 25 May 2000 (25.05.00).
 - ii. ☐ by applicant on (date) _____.
3. ☒ A translation of the International application into the English language [35 USC 371(c)(2)]:
 - a. ☐ is transmitted herewith.
 - b. ☒ is not required as the application was filed in English.
 - c. ☐ was previously transmitted by applicant on (date) _____.
 - d. ☐ will follow (within 32 months of earliest priority date).
4. ☒ Amendments to the claims of the International application under PCT Article 19 [35 USC 371(c)(3)]:
 - a. ☐ are transmitted herewith.
 - b. ☐ have been transmitted
 - i. ☐ by the International Bureau. Date of mailing of the amendment (from form PCT/IB/308): _____.
 - ii. ☐ by applicant on (date) _____.
 - c. ☒ have not been transmitted as
 - i. ☒ applicant chose not to make amendments under PCT Article 19. Date of mailing of Search Report (from form PCT/ISA/210): 22 February 2000 (22.02.00).
 - ii. ☐ the time limit for the submission of amendments has not yet expired. The amendments or a statement that amendments have not been made will be transmitted before the expiration of the time limit under PCT Rule 46.1.

5. [x] A translation of the amendments to the claims under PCT Article 19 [35 USC 371(c)(3)]:
- [] is transmitted herewith.
 - [] is not required as the amendments were made in the English language.
 - [x] has not been transmitted for reasons indicated at point 4c above.
6. [x] A copy of the International Preliminary Examination Report (PCT/IPEA/409)
- [x] is transmitted herewith.
 - [] is not required as the application was filed with the United States Receiving Office.
7. [x] Annex(es) to the International Preliminary Examination Report
- [x] is/are transmitted herewith.
 - [] is/are not required as the application was filed with the United States Receiving Office.
 - [] is/are not being transmitted as there is/are no Annex(es).
8. [x] A translation of the annexes to the International Preliminary Examination Report
- [] is transmitted herewith.
 - [x] is not required as the annexes are in the English language.
 - [] is not being transmitted for the reason indicated at point 7c above.
9. [x] An oath or declaration of the inventor [35 USC 371(c)(4)] complying with 35 USC 115
- [] was previously submitted by applicant on (date) _____.
 - [] is submitted herewith and such oath or declaration
 - [] is attached to the application

ii. ☐ identifies the application and any amendments under PCT Article 19 which were transmitted as stated in points 4a or b; and states that they were reviewed by the inventor as required by 37 CFR 1.70.

c. ☒ will be provided in response to a Notice to File Missing Requirements.

10. ☒ An International Search Report (PCT/ISA/210) or Declaration under PCT Article 17(2)(a):

a. ☐ is transmitted herewith.

b. ☒ has been transmitted by the International Bureau. Date of mailing (from form PCT/IB/308): 25 May 2000 (25.05.00).

c. ☐ is not required as the application was searched by the United States International Searching Authority.

d. ☐ will be transmitted promptly upon request.

e. ☐ has been submitted by applicant on (date) _____.

11. ☐ An Information Disclosure Statement under 37 CFR 1.97 and 1.98:

a. ☐ is transmitted herewith.

Also transmitted herewith is

☐ Form PTO-1449

☐ Copies of citations listed

b. ☐ will be transmitted within THREE MONTHS of the date of submission of requirements under 35 USC 371(c).

c. ☐ was previously submitted by applicant on (date) _____.

12. ☐ The applicant claims small entity status with respect to this application.

☐ A Verified Statement Claiming Small Entity Status is attached.

☐ The undersigned claims small entity status on behalf of the applicant.

-
-
-

1. 2.

SMITH-HILL & BEDELL, P.C.
12670 N.W. Barnes Road, Suite 104
Portland, Oregon 97229

(Transmittal Letter to the United States Elected Office (EO/US) page 5 of 5)

FEE CALCULATION SHEET

Entry into National Phase of PCT/GB99/03785

CLAIMS FEE	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
* [x]	TOTAL CLAIMS 25	-20 =	5	x \$ 18 =	\$ 90
	INDEPENDENT CLAIMS 1	- 3 =	0	x \$ 80 =	\$ 0
	MULTIPLE DEPENDENT CLAIM(S) (if applicable)			+ \$270 =	\$ 0
BASIC FEE	<input type="checkbox"/> U.S. PTO WAS INTERNATIONAL PRELIMINARY EXAMINATION AUTHORITY Where an International preliminary examination fee as set forth in § 1.482 has been paid on the international application to the U.S. PTO <input type="checkbox"/> and the international preliminary examination report states that the criteria of novelty, inventive step (non-obviousness) and industrial activity, as defined in PCT Article 33(1) to (4) have been satisfied for all the claims presented in the application entering the national state (37 CFR 1.492(a)(4)) \$100 <input type="checkbox"/> and the above requirements are not met (37 CFR 1.492(a)(1)) \$690 <input checked="" type="checkbox"/> U.S. PTO WAS NOT INTERNATIONAL PRELIMINARY EXAMINATION AUTHORITY Where no international preliminary examination fee as set forth in § 1.482 has been paid to the U.S. PTO, and payment of an international search fee as set forth in § 1.445(a)(2) to the U.S. PTO: <input type="checkbox"/> has been paid (37 CFR 1.492(a)(2)) \$710 <input type="checkbox"/> has not been paid (37 CFR 1.492(a)(3)) \$1,000 <input checked="" type="checkbox"/> where a search report on the international application has been prepared by the European Patent Office or the Japanese Patent Office (37 CFR 1.492(a)(5)) \$860				860
OTHER FEES	Surcharge of \$130 for furnishing the oath or declaration later than 30 months (but no later than 32 months) from any claimed priority date (37 CFR 1.492(e) and 37 CFR 1.495(c)).				+
	Total of above Calculations				= 950
SMALL ENTITY	Reduction by 1/2 for filing by small entity, if applicable. Affidavit must be filed also. (note 37 CFR 1.9, 1.27, 1.28)				-
	Subtotal				950
	Processing fee of \$130 for furnishing the English Translation later than 30 months (but not later than 32 months) from any claimed priority date (37 CFR 1.492(f) and 37 CFR 1.495(c)).				+
	Total National Fee				\$ 950
	Fee for recording the enclosed assignment document \$40 (37 CFR 1.21(h)).				+
TOTAL	TOTAL FEES ENCLOSED				\$ 950

* See attached Preliminary Amendment.

[x] A check in the amount of \$950 to cover the above fees is enclosed.

[x] Please charge any additional basic filing fees under 37 CFR 1.492(a) which may be required by this paper, or credit any overpayment to Deposit Account No. 19-2560. This sheet is filed in duplicate.

Penelope Stockwell
 Penelope Stockwell

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of

David COLEY

Art Unit:

Application No:

Examiner:

Filed:

For: ACTUATOR APPARATUS

PRELIMINARY AMENDMENT

Commissioner for Patents
Washington, D.C. 20231

Sir:

Please make the following amendments to this application
prior to examination thereof.

AMENDMENTS

In the Claims:

Claims 4-26, cancel.

Add new claims as follows:

27. (New) Apparatus according to claim 1, characterized
in that the valve means has a port having a width which is not
constant in the axial direction of the valve arrangement,
whereby the effective width of the fluid path to the piston
means can be set by setting the axial position of the valve
arrangement.

28. (New) Apparatus according to claim 1, characterized
in that the valve arrangement provides drive alternatively to
opposite faces of a piston of the piston means, whereby to
create reciprocation.

29. (New) Apparatus according to claim 1, characterized
in that the valve arrangement is formed to complete a
plurality of cycles of the piston means for each full turn of
the valve arrangement.

30. (New) Apparatus according to claim 29, characterized in that the valve arrangement has a first axial position in which a first number of cycles are completed for each full turn of the valve arrangement and a second axial position in which a different number of cycles is completed for each full turn.

31. (New) Apparatus according to claim 30, characterized in that the fluid path to the piston means is relatively narrow in the first axial position, and relatively wide in the second axial position.

32. (New) Apparatus according to claim 1, characterized by further comprising intermediate means to which driving forces are provided by the piston means, and which convey driving forces to an item being driven.

33. (New) Apparatus according to claim 32, characterized in that the item is an item of tooling or a pile element.

34. (New) Apparatus according to claim 32, characterized in that the intermediate member provides for movement to align the tooling.

35. (New) Apparatus according to claim 34, characterized in that the alignment movement is provided hydraulically or pneumatically.

36. (New) Apparatus according to claim 32, characterized in that the intermediate member conveys forces to clamping members by which a workpiece is clamped, in use.

37. (New) Apparatus according to claim 32, characterized in that the clamping members extend at an angle to the intermediate means to allow side or end clamping of a workpiece.

38. (New) Apparatus according to claim 32, characterized in that the intermediate means is elongate.

39. (New) Apparatus according to claim 38, characterized in that the intermediate means extends to one side of the common member.

40. (New) Apparatus according to claim 37, characterized in that the clamping members extend substantially perpendicular to the intermediate means.

41. (New) Apparatus according to claim 32, characterized in that the intermediate means extend through a passage within the piston means, and have enlarged heads against which the piston means may act in either of two opposite directions.

42. (New) Apparatus according to claim 1, characterized by comprising resilient members against which the piston means acts, in use.

43. (New) Apparatus according to claim 42, characterized in that the piston means are isolated by the resilient members from direct impacts, whereby to create vibratory driving forces.

44. (New) Apparatus according to claim 42, characterized in that the piston means create impact forces when the resilient members are fully compressed.

45. (New) Apparatus according to claim 1, characterized in that the apparatus is adapted for resilient attachment to a mounting arrangement by means of which the apparatus may be supported by a conventional support arrangement.

46. (New) Apparatus according to claim 45, characterized in that the support arrangement is provided by a conventional excavator or like machine.


47. Apparatus according to claim 46, characterized in that the support machine is operable to apply crowd forces to the apparatus.

48. Apparatus according to claim 46, characterized in that the support machine is able to supply pressurized fluid to the apparatus.

REMARKS

The above amendments are presented in order to place this application in better condition for examination.

Respectfully submitted,



John Smith-Hill
Reg. No. 27,730

SMITH-HILL & BEDELL, P.C.
12670 N.W. Barnes Road, Suite 104
Portland, Oregon 97229

Tel. (503) 574-3100
Fax (503) 574-3197

Docket: SWIN 2241

09/831488

JCO3 Rec'd PCT/PTL 09 MAY 2001

Abstract

An actuator (10) for use in installing or extracting piles and the like has a common member (12) supported at (14) and having jaws (16) for gripping a pile. Within the block (12) a double-acting piston (18) is located alongside a space (20) for a control valve arrangement which provides hydraulic fluid, in various ways described, to create vibratory or impact forces from the piston (18). The piston and the valve arrangements are both removable and replaceable by alternatives, to modify the mode of operation of the actuator (10).

FILED IN 831488

Actuator Apparatus

The present invention relates to actuator apparatus and in particular, but not exclusively, to hydraulic apparatus for installing or extracting pile elements and like members by vibration or impact.

The apparatus may be used with pile elements as defined in British Standard specification BS EN 996; 1996 entitled "Piling Equipment - Safety Standards". Piles and like members are driven into the ground for a variety of reasons in the construction industry and other industries. In addition to pile elements as defined in BS EN 996, other types of element are conventionally installed in a similar manner, such as steel trench sheeting, and PVC, polystyrene and glass fibre composite piles. These may be used for shoring up a trench wall, protection against erosion, etc. Devices may also be driven in a similar manner for soil compaction.

For simplicity, the single term "pile element" is used in a broader manner in this specification than in BS EN 996, in order to encompass all of these alternatives and similar items drivable into the ground. In addition, apparatus may be used to withdraw members from the ground by applying forces in the opposite direction. Again for simplicity, the term "installation" is used herein to refer to the application of forces for causing items to be forced down against resistance provided by the ground, or to penetrate the ground, "extraction" is used to refer to the application of forces for causing items to be withdrawn from the ground, and "driving" is used to refer to installation and extraction.

Various devices have been proposed for providing driving forces, by vibration, impact or the application of static forces. The nature and magnitude of forces to be used will in practice be chosen according to a number of factors, including the soil type and the nature of the pile element being driven. For instance, in loose, non-cohesive soils, vibration is often the quickest and quietest technique. Relatively high frequency vibration is generally attenuated

more quickly and is therefore preferable for use near populated areas, particularly brown field sites. Other soil types are better served by impact driving, but this can cause problems from noise and shock waves. Legislation, particularly concerning health and safety, is becoming increasingly strict in respect of vibration and noise created by piling operations, and this presents a further factor influencing the choice of technique.

It is therefore conventional to build apparatus in a variety of different sizes and operating in a variety of different ways, so that an appropriate apparatus can be chosen for a particular situation. Unfortunately, problems with delay can then occur if it is found that the choice was inappropriate. Alternatively, equipment may be provided unnecessarily, so that alternatives are available on-site if required, but remain unused if not.

The present invention seeks to obviate or mitigate these or other disadvantages of the prior art.

The invention provides actuator apparatus comprising piston means operable to create driving forces from a supply of pressurised fluid, and valve means operable to supply pressurised fluid to the piston means according to a predetermined sequence, to cause the apparatus to execute a first operation, the valve means and the piston means being housed within a common member, and the apparatus being characterised in that the valve means or the piston means or both being removable from the member for replacement by an alternative means operable within the common member to cause the apparatus to execute an alternative operation, and wherein the or each valve means comprise a valve arrangement rotatable within a housing, there being ports in the housing walls for pressurised fluid, and the valve arrangement carrying partitions which serve to change the connections between the fluid ports in accordance with the predetermined sequence as the valve arrangement rotates, and wherein the valve arrangement of the or at least one of the valve means is axially movable to change the predetermined sequence.

ART 34 AMDT

We have realised that an actuator according to the invention can be used to apply vibration, impact or static forces to pile elements and also to tooling such as a compaction plate, an auger or mandrel, or demolition shears or cutters. Preferably the valve means is removable for replacement with an alternative valve means operable to supply fluid according to an alternative sequence. The valve arrangement may have a first axial position at which a wider fluid path is provided to one face of the piston means than to the other, and be movable to a second axial position at which a narrower fluid path is provided to the said one face than to the other. The valve means may have a port having a width which is not constant in the axial direction of the valve arrangement, whereby the effective width of the fluid path to the piston means can be set by setting the axial position of the valve arrangement. The valve arrangement may provide drive alternatively to opposite faces of a piston of the piston means, whereby to create reciprocation.

The valve arrangement may be formed to complete a plurality of cycles of the piston means for each full turn of the valve arrangement. The valve arrangement may have a first axial position in which a first number of cycles are completed for each full turn of the valve arrangement and a second axial position in which a different number of cycles is completed for each full term. The fluid path to the piston means may be relatively narrow in the first axial position, and relatively wide in the second axial position.

The apparatus may further comprise intermediate means to which driving forces are provided by the piston means, and which convey driving forces to an item being driven. The item may be an item of tooling or a pile element. The intermediate member may provide for movement to align the tooling and may be operable hydraulically or pneumatically. The intermediate member may convey forces to clamping members by which a workpiece may

be clamped. The clamping members preferably extend at an angle to the intermediate means to allow side or end clamping of a workpiece. The intermediate means is preferably elongate, and preferably extends to one side of the common member. The clamping members may extend substantially perpendicular to the intermediate means.

The intermediate means may extend through a passage within the piston means, and have one or more enlarged heads against which the piston means may act in either of two opposite directions.

Resilient members may be provided, against which the piston means acts, in use. The piston means may be isolated by the resilient members from direct impacts, whereby to create vibrating driving forces. The piston means may create impact forces when the resilient members become fully compressed.

The apparatus is preferably adapted for resilient attachment to a mounting bracket by means of which the apparatus may be supported by a conventional support arrangement. The support arrangement may be provided on a support machine, preferably operable to apply crowd forces to the apparatus and preferably able to supply pressurised fluid to the apparatus.

Embodiments of the present invention will now be described in more detail, by way of example only, and with reference to the accompanying drawings, in which:-

Fig. 1 is a simplified side elevation of an actuator according to the present invention;

Fig. 2 is a plan view of the actuator of Fig. 1;

Fig. 3 is a vertical section through the actuator of Fig. 1;

Fig. 4 is a more detailed cut-away view, on an enlarged scale;

Figs. 5 to 8 are sections through alternative valve arrangements;

Fig. 9 is a view corresponding with Fig. 4 and showing an alternative piston arrangement;

Fig. 10 is a view corresponding with Fig. 4 and showing a further alternative piston arrangement;

Fig. 11 is a view corresponding with Fig. 4 and showing a still further piston arrangement; and

Figs. 12 to 14 are simple elevations of the actuator of Figs. 1 to 3 being used with various types of tooling arrangement according to the invention.

Turning first to Figs. 1 to 3, there is shown an actuator 10 for use in installing or extracting piles and the like. The actuator 10 has a common block 12 supported at 14, as will be described, and having jaws 16 for gripping a pile. Within the block 12, the actuator 10 has a double-acting piston 18 alongside which there is a space 20 for a control valve arrangement (omitted from Fig. 3 for clarity) which provides hydraulic fluid to the piston 18, during use.

The block 12 is supported at 13 by resilient mountings on a mounting bracket 15, which is in turn mounted at 14 on the second bracket 22 of an excavator or like hydraulic machine. The second bracket 22 carries a vertical hinge pin 24 by fingers 26. A second set of fingers 28 attach the bracket 15 to the pin 24, which is rotatable relative to the fingers 26, allowing the machine 10 to be turned relative to the second bracket 22, about a generally vertical axis. Alternatively, hinge arrangement can be replaced by an arrangement of a swivel pin and thrust bearings. These arrangements make use of the apparatus 10 more versatile, by allowing operation at a variety of angles and in confined

spaces. The hinge arrangement could be more compact than is shown.

The second bracket 22 is preferably mounted on the arms of an excavator or like machine, preferably one which can apply a downward force ("crowd") to the machine 10 while in use, to assist in driving a pile. The presence of resilient mountings at 13 helps isolate the excavator from impact and vibration created within the machine 10.

The bottom end of the piston 18 carries a plate 30 from which the jaws 16 project. One jaw, 16A is fixed in position. The other jaw is mounted at a pivot 32 part way along its length. A clamp piston 34 is provided, acting between the free end of the jaw 16B, and the fixed jaw 16A or a fixed point on the plate 30. Consequently, pressurising the piston 34 to extend the piston arm will cause the jaw 16B to pivot at 32 and move toward the jaw 16A, to clamp a workpiece 36, generally at 38, between gripping plates 39 carried by the jaws 16. It can be seen from the drawings that the jaws 16 reach out sideways (i.e. generally horizontally and transverse to the driving direction) to reach the pile 36. The plates 39 reach down from the ends of the jaws 16, extending below any other part of the machine 10. This increases versatility of the device in allowing a pile member to be gripped from the side or from above. When gripped from the side, the whole of the plate 39 can be used, which reduces the pressure applied by the plates, while allowing adequate driving forces to be conveyed. This is particularly preferred for relatively fragile pile members such as light metal trench sheeting, wooden or concrete sections, glass fibre or PVC pile members. Side driving allows driving even if the top of the pile is beyond the reach of the excavator arms on which the apparatus is mounted. However, end driving can be achieved by locating the machine 10 above the pile member, which is gripped between the lower extremities of the plates 39.

The piston 18 shown in Fig. 3 is of generally cylindrical form, movable in a generally vertical direction in bores 40 and a central chamber 42. The piston 18 carries a shoulder 44 within the chamber 42. The diameter of the piston 18 is smaller above the shoulder 44 than below, so that the surface area of the

shoulder 44 transverse to the piston axis is greater on the upper surface of the shoulder 44 than on the lower surface.

Upper and lower hydraulic ports 46, 48 communicate between the chamber 42 and the valve space 20, allowing valve arrangements (to be described) to provide hydraulic fluid to the upper or lower face of the shoulder 44, in order to drive a piston up or down.

In Figs. 1 to 3, the piston 18 is permanently affixed to the plate 30 by means of attachment pins 50, so that reciprocating vertical movement of the piston 18 causes vibration of the plate 30, and thus allows a pile 36 to be driven by vibration.

The arrangement shown in Fig. 4 is very similar to the arrangement of Fig. 3, but shows an alternative piston 18B which is no longer permanently attached to the plate 30. Rather, the lower face 52 can move up, clear of the upper face 54 of an anvil 55 attached to the plate 30, in place of the piston, by means of the pins 50. The face 52 can also move down to strike the face 54, so that impact (or "percussive") forces are generated in this arrangement. The anvil 55 is supported from below by a compression spring arrangement 57, which serves to push the anvil 55 up into the block 12 after each strike. The spring arrangement 57 also serves to isolate the main body of the machine from shock forces.

Fig. 4 illustrates a valve arrangement 56 located in the space 20. The arrangement 56 is a rotary valve arrangement driven by a motor 58 (which may be a hydraulic motor) through a shaft 60 to which various components (including the motor) are splined. Bearings 62 are provided to support components of the arrangement 56 during rotation. Splines connect the various rotating components and also allow axial movement, for reasons to be explained below. It will become apparent that at least in some examples, particularly those in which axial movement is not required, splined connections may not be required.

The valve arrangement 56 is in the form of a removable cartridge, and has an inlet 64 for pressurised hydraulic fluid, and an exhaust outlet 66. The inlet 64 communicates with an inner space 68 around the shaft 60 and bounded at its outer extremity by partitions 70. However, two outlets 72 are provided from the inner space 68. The upper outlet 72A is in communication with the upper port 46 when the arrangement 56 is in the rotary position as shown in Fig. 4. The lower outlet 72B is closed by the walls of the valve arrangement. Thus, in this position, hydraulic pressure is being supplied to the upper face of the shoulder 44, driving the piston 18 downwardly. However, it can readily be seen from Fig. 4 that after the valve arrangement 56 has turned through 180° about the shaft 60, the upper outlet 72A will have moved clear of the upper port 46, and the lower outlet 72B will have come into communication with the lower port 48. In this position, hydraulic pressure passes to the lower face of the shoulder 44, driving the piston 18 upwardly, for the return stroke. It can be appreciated that with the surface area of the upper face of the shoulder 44 being greater than the surface area of the lower face, the piston 18 is driven downwardly with greater force than it is returned upwardly.

The valve arrangement 56 also provides a return path for hydraulic fluid to exhaust at 66. An outer space 74 extends around the partition 70 and communicates at 76 with the exhaust bore 66. The exhaust port 76 will not communicate with the pressure source 64 or outlets 72 at any angular position of the valve arrangement. Thus, in the position shown in Fig. 4, the lower port 48 is connected through the outer space 74 to the exhaust 66. After the arrangement 56 turns through 180° , the upper port 46 will be in communication with the outer space 74, allowing hydraulic fluid to pass around the partition 70, to reach the exhaust 66. Thus, by applying hydraulic pressure to the inlet 64 and allowing exhausting through the exhaust 66, while turning the valve arrangement 56, the piston 18 is reciprocated by alternately applying pressure above and below the shoulder 44, while exhausting the other face of the shoulder 44.

The valve arrangement shown in Fig. 4 represents a relatively simple

operating sequence, appropriate for simple impact installation of a pile member clamped in the jaws 16, but not for extraction. However, an extraction arrangement can be formed by replacing the piston with one having a larger lower face and smaller upper face, and by attaching the piston to the plate 30 in place of the anvil 55, in the manner of Figs. 1 to 3. In other circumstances, alternative operating sequences may be required. In particular, the operating sequence may require to be different if impact is used rather than vibration, or according to the nature of the pile element being driven or the ground into which it is being installed or from which it is being extracted. For all of these reasons, and in accordance with the invention, the valve arrangement 56 is replaceable in the piling machine 10, by removal of a closure plate 80, so that the valve arrangement 56 can be withdrawn as a single unit, sliding up the splined motor shaft 60. A replacement cartridge containing an alternative valve arrangement 56 can then be placed into the space 20, to change the operating sequence of the machine 10, as will now be described with particular reference to Figs. 5 to 8, which show alternative valve arrangements in isolation.

In each of Figs. 5 to 8, there is shown a vertical section through the valve arrangement, corresponding to the view in Fig. 4, together with inset views of sections at various positions. In each case, the horizontal section is labelled with a suffix corresponding to the section line in the main drawing so that, for instance, Fig. 5B is a horizontal section at the line B-B in Fig. 5. In addition, it must be understood that the section views are sections "at" the corresponding height, not "from" the corresponding height, so that only those components present at the section plane are shown in the section drawing.

The arrangement 56A in Fig. 5 differs from that in Fig. 4 principally in that two cycles of the piston 18 are produced for each complete revolution of the valve 56A. This is achieved by providing two upper outlets 82A from the inner space 68A, at 180° from each other. Partitions 84A separate the upper outlets 82A from upper extensions 86 of the outer space 74A. Similar partitions 84B are provided at the height of the lower outlet 72B, so that in the condition shown, the outer space 74A communicates with the port 72B to

connect this with the vent 66, while the upper outlet 82A is coupled through the inner space 68A to the inlet 64. This provides the down stroke of the piston 18.

As the valve arrangement turns through 90°, including the partitions 84A, 84B, the inner space 68A and positive hydraulic pressure comes in communication with the lower port 82B between the partitions 84B, whereas the outer space 86 around the partitions 84A comes into communication with the upper port 72A, so that the return stroke commences, with hydraulic pressure being supplied under the piston 18. After a second 90° turn of the valve arrangement, the arrangement reverses again, creating a second down stroke. Consequently, this valve arrangement creates an operating frequency which is twice the frequency of the arrangement of Fig. 4 (at a given motor speed).

Fig. 6 shows a more complex arrangement in which the partition elements within the valve arrangement are axially movable, with the sequence performed by the valve being changed according to the axial position, as follows.

The arrangement 56B has some similarities to the arrangement 56 (Fig. 4) in that each full turn of the arrangement 56B produces one complete cycle of the piston 18. However, the axial position of the arrangement 56B allows the cycle to use either a wide supply to the port 46 and a narrow supply to the port 48 (for a powerful down stroke and a relatively weak up stroke, such as for installing pile members), or a wide supply to the port 48 and a relatively narrow supply to the port 46 (for a strong up stroke and a relatively weak down stroke, such as for use in extraction of pile members). These alternatives are achieved with replacing the piston, as follows.

The upper outlet 88A is divided at a horizontal plane by a divider 90A, leaving a relatively wide mouth above the divider 90A, and a relatively narrow mouth below. In the axial position shown in Fig. 6, it is the relatively wide

mouth above the divider 90A which comes into communication with the outlet port 89A on each revolution. However, if the arrangement 56B is moved up to bring the divider 90A to the top of the outlet 88A, it will then be the relatively narrow mouth below the divider 90A which comes into communication with the outlet port 89A.

In similar manner, the lower outlet 88B is horizontally divided by a divider 90B, with a relatively wide mouth below the divider 90B, and a relatively narrow mouth above. In the axial position shown in Fig. 6, it is the relatively narrow mouth above the divider 90B which comes into communication with the outlet port 89B, but if the arrangement 56B is moved up to bring the divider 90B to the top of the port 89B, the wide mouth below the divider 90B will then come into communication with the port 89B on each revolution.

By virtue of this arrangement, the sequence of the piston 18 can be "reversed", either to provide strong downward forces for installation, or strong upward forces for extraction.

The axial position of the arrangement 56B is set by a vertical drive arrangement 92 controlled through a valve 94 which allows the arrangement 56B to be driven upwardly, downwardly or locked in position.

Fig. 7 shows a further alternative valve arrangement 56C. In this arrangement, the axial position can be selected to choose between either a high frequency, low amplitude oscillation or a low frequency, high amplitude oscillation. During pile driving, low frequency may be preferred for its effectiveness, but gives rise to vibrations which travel further than higher frequencies. Higher frequencies are less problematic from this point of view, but generally less effective for driving. An advantage of the arrangement 56C is that high or low frequency can readily be chosen according to the operating conditions, simply by changing the axial position, as follows.

The arrangement of Fig. 7 has some similarities with Fig. 5, in that two upper outlets 104A are provided at diametrically opposite positions, to produce two down strokes for each rotation of the arrangement 56C. The upper outlets 104A are relatively narrow. Consequently, the sequence of the piston 18 is relatively high frequency, but low in amplitude.

One of the upper outlets 104A (the left hand outlet as shown in Fig. 8) is separated from a wider outlet 104C by a divider 106. The arrangement 56C can be raised from the position shown until the outlet 104C is at the appropriate height to come into communication with the port 107 on each revolution of the arrangement. That has the effect of halving the frequency of the sequence, but the relatively wide outlet 104C creates relatively high amplitude movement of the piston 18.

Fig. 8 shows a further alternative valve arrangement 56D in which the axial position is again relevant. Again, the arrangement 56D is broadly similar to the arrangement shown in Fig. 4, in that one cycle of the piston 18 is created by each full turn of the valve arrangement 56D. However, the upper outlet 96A is significantly different to the corresponding parts previously described, as can be seen from Fig. 7C. The circumferential width of the outlet 96A reduces with increasing height up the axis of the arrangement 56D. The outlet 96A is broadly triangular. The axial length of the outlet 96A is greater than the axial length of the port 100 in the wall. Consequently, the total area through which the inner space 102 can communicate with the port 100 will depend on the vertical position of the triangular outlet 96A. As the arrangement 56D moves axially upwardly, the area increases, which reduces the restriction on hydraulic fluid and thus allows a greater volume of hydraulic fluid to pass within the time allowed by the turning of the arrangement 56D. In consequence, a higher axial position corresponds with a larger amplitude of piston movement, and this amplitude is continuously adjustable by setting the axial position of the arrangement 56D.

It can readily be understood that the various valve arrangements shown

in Figs. 4 to 8 are interchangeable thus giving the apparatus a modular format and allowing apparatus to be readily adapted for different operating requirements.

Fig. 9 shows a modification relating to the piston. The piston 18C of Fig. 9 has a hollow bore 107 through which the anvil 55A extends, having enlarged heads above and below the piston 18C. Return springs 57A, 57B bear on the anvil 55A from above and below. Consequently, and depending on the nature of the valve cartridge being used, the piston member 18C can be driven to impact on the upper head or on the lower head. Impact on both heads is not desirable. It is particularly preferred to use the valve arrangement illustrated in Fig. 6, which provides asymmetric fluid supply so that the unit will operate either for installation or extraction. In the condition shown, with the piston 12C free to slide relative to the anvil 55A, the operation is by impact, but an arrangement could be provided to lock the piston 18C to the anvil 55A to produce operation by vibration.

Fig. 10 shows a further modification, again relating to the piston. In other respects, the version of Fig. 10 is equivalent to the version of Fig. 9. In Fig. 10, the piston 18D again has a hollow bore 107 through which the anvil 55A extends, the anvil having enlarged heads above and below the piston 18D. Springs 57C, 57D are provided in the form of coil compression springs located around the shaft of the anvil 55A, bearing between the anvil heads and the piston 18D. Consequently, and depending upon the nature of the valve cartridge being used, the piston member 18D can be driven toward the upper head or the lower head of the anvil 55A, which will cause the springs 57C, 57D to become compressed. Oscillation of the piston 18D will therefore cause vibration of the anvil 55A, resulting in vibratory driving forces. However, if resistance is met, such as unusually hard ground, the piston 18D may fully compress one or other of the springs 57C, 57D, resulting in an impact between the piston 18D and one or other anvil head. This causes impact forces to be created and conveyed to the workpiece. This arrangement can be used to drive and extract pile elements, by use of an appropriate valve cartridge.

Fig. 11 shows a further modification, which makes use of the valve cartridge of Fig. 4. This modification can make use of a solid piston 18E, as shown, similar to the piston of Fig. 4, or a piston with a hollow bore, similar to the piston 18C, 18D of Figs. 9 and 10. In this example, a powerful spring 57E acts between the piston 18E and the top wall of the piston chamber 42E. The spring 57E is a compression spring acting to push the piston 18E down toward the anvil 55E. Using an adequately strong spring 57E, the piston 18E will be kept in contact with the anvil 55E during normal use, so that reciprocation of the piston 18E relative to the block 12 will cause vibration of the anvil 55E and thus of the item gripped by the jaws 16 or otherwise attached (see below). However, if the spring force is overcome, particularly in adverse conditions, the piston 18E may be moved clear of the anvil 55E, so that on the downward stroke of the piston 18E, there will be an impact between the piston 18E and the anvil 55E, the force of the impact being equal to the sum of the force provided by the hydraulic supply to the chamber 42E, and the return force of the spring 57E. An arrangement of the nature of Fig. 11 is capable only of creating downward forces for installation, not for extraction.

The remaining drawings illustrate the use of an actuator according to the present invention with various types of tooling. In Fig. 12, the actuator 10 of Figs. 1 to 3 is permanently attached to a pulveriser device 120 by replacement of the plate 30. The pulveriser 120 has a leg 122 extending downwardly from the actuator 10 and turning sideways to form a lower jaw 124 of a pulveriser mouth 126. The upper jaw 128 is preferably serrated. A hydraulic cylinder 129 acts between the upper jaw 128 and the leg 122 to open and close the mouth 126. The effectiveness of the jaws is further enhanced by the vibratory or impact forces created by the actuator 10 (according to the nature of the piston and valve cartridge in use).

Fig. 13 shows the pulveriser 120 replaced by an elongate, downwardly extending mandrel attachment 130 by which vibratory or impact forces created by the actuator 10 can be conveyed down a bore formed in the ground, for instance.

ART 34 AMDT

項目	単位	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2423	2424	2425	2426	2427	2428	2429	2430	2431	2432	2433	2434	2435	2436	2437	2438	2439	2440	2441	2442	2443	2444	2445	2446	24
----	----	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	----

It will be apparent that many variations and modifications can be made to the apparatus as described above without departing from the scope of the present invention. In particular, many features can be used interchangeably in combinations other than those described, which is a particular benefit of the invention. The block member could be assembled from more than one part. Many other piston operation sequences could be devised by appropriate modification of valve arrangements, so that operation of a machine can be modified at will by the simple expedient of appropriate modification to the valve assembly, thus retaining the machine flexible in its application.

ART 34 AMDT

CLAIMS

1. Actuator apparatus (10) comprising piston means (18) operable to create driving forces from a supply of pressurised fluid, and valve means (56) operable to supply pressurised fluid to the piston means according to a predetermined sequence, to cause the apparatus to execute a first operation, the valve means and the piston means being housed within a common member (12), and the apparatus being characterised in that the valve means or the piston means or both being removable from the member for replacement by an alternative means operable within the common member to cause the apparatus to execute an alternative operation, and wherein the or each valve means comprise a valve arrangement rotatable within a housing (20), there being ports (64,66,72,82,88, 89,100,104,107) in the housing walls for pressurised fluid, and the valve arrangement carrying partitions (84) which serve to change the connections between the fluid ports in accordance with the predetermined sequence as the valve arrangement rotates, and wherein the valve arrangement of the or at least one of the valve means is axially movable to change the predetermined sequence.
2. Apparatus (10) according to claim 1, characterised in that the valve means (56) is removable for replacement with an alternative valve means operable to supply fluid according to an alternative sequence.
3. Apparatus (10) according to claim 1, characterised in that the valve arrangement (56) has a first axial position at which a wider fluid path is provided to one face of the piston means (18) than to the other, and is movable to a second axial position at which a narrower fluid path is provided to the said one face than to the other.
4. Apparatus (10) according to claim 1, 2 or 3, characterised in that the valve means (56) has a port (96A) having a width which is not constant in the axial direction of the valve arrangement, whereby the effective width of the fluid path to the piston means (18) can be set by setting the axial position of the

ART 34 AMDT

valve arrangement.

5. Apparatus (10) according to any preceding claim, characterised in that the valve arrangement (56) provides drive alternatively to opposite faces of a piston (18) of the piston means, whereby to create reciprocation.

6. Apparatus (10) according to any preceding claim, characterised in that the valve arrangement (56) is formed to complete a plurality of cycles of the piston means (18) for each full turn of the valve arrangement.

7. Apparatus (10) according to claim 6, characterised in that the valve arrangement (56) has a first axial position in which a first number of cycles are completed for each full turn of the valve arrangement and a second axial position in which a different number of cycles is completed for each full term.

8. Apparatus (10) according to claim 7, characterised in that the fluid path to the piston means (18) is relatively narrow in the first axial position, and relatively wide in the second axial position.

9. Apparatus (10) according to any preceding claim, characterised by further comprising intermediate means (30) to which driving forces are provided by the piston means (18), and which convey driving forces to an item (38) being driven.

10. Apparatus (10) according to claim 9, characterised in that the item (38) is an item of tooling or a pile element.

11. Apparatus (10) according to claim 9 or 10, characterised in that the intermediate member (30) provides for movement to align the tooling.

12. Apparatus (10) according to claim 11, characterised in that the alignment movement is provided hydraulically or pneumatically.

ART 34 AMDT

18

13. Apparatus (10) according to any of claims 9 to 12, characterised in that the intermediate member (30) conveys forces to clamping members (16) by which a workpiece (38) is clamped, in use.
14. Apparatus (10) according to any of claims 9 to 13, characterised in that the clamping members (16) extend at an angle to the intermediate means (30) to allow side or end clamping of a workpiece (38).
15. Apparatus (10) according to any of claims 9 to 14, characterised in that the intermediate means (30) is elongate.
16. Apparatus (10) according to claim 15, characterised in that the intermediate means (30) extends to one side of the common member (12).
17. Apparatus (10) according to claim 14, 15 or 16, characterised in that the clamping members (16) extend substantially perpendicular to the intermediate means (30).
18. Apparatus (10) according to any of claims 9 to 17, characterised in that the intermediate means (30) extend through a passage (107) within the piston means, and have enlarged heads against which the piston means (18) may act in either of two opposite directions.
19. Apparatus (10) according to any preceding claim, characterised by comprising resilient members (57) against which the piston means (18) acts, in use.
20. Apparatus (10) according to claim 19, characterised in that the piston means (18) are isolated by the resilient members (57) from direct impacts, whereby to create vibratory driving forces.
21. Apparatus (10) according to claims 19 or 20, characterised in that the piston means (18) create impact forces when the resilient members (57) are fully

ART 34 AMDT

compressed.

22. Apparatus (10) according to any preceding claim, characterised in that the apparatus is adapted for resilient attachment to a mounting arrangement (15) by means of which the apparatus may be supported by a conventional support arrangement (22).

23. Apparatus (10) according to claim 22, characterised in that the support arrangement (22) is provided by a conventional excavator or like machine.

24. Apparatus (10) according to claim 23, characterised in that the support machine is operable to apply crowd forces to the apparatus.

25. Apparatus (10) according to claim 23 or 24, characterised in that the support machine is able to supply pressurised fluid to the apparatus.

26. Actuator apparatus substantially as described above, with reference to the accompanying drawings.

P00220 337E000




FIG. 1




FIG. 2




FIG. 3






FIG. 5




FIG. 5A




FIG. 5B




FIG. 6




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 7




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 8




FIG. 8A




FIG. 8B




FIG. 8C






FIG. 9



FILE 11

**FIG. 12**





Fig. 13

**FIG. 14**

Attorney's Docket No. SWIN 2241

DECLARATION FOR PATENT APPLICATION
(COMBINED WITH POWER OF ATTORNEY)
(ORIGINAL APPLICATION)

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name. I believe I am the original, first, and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

ACTUATOR APPARATUS

the specification of which is attached hereto unless box (a) or (b) is checked, in which case

- (a) ☐ the specification was filed on _____ as Application No. _____.
- (b) ☒ the specification was filed as PCT International Application No. PCT/GB99/03785 filed on November 12, 1999 and was amended under PCT Art. 19 on _____ (if any).


I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose to the Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Sec. 1.56.

I have identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America and filed less than 12 months (6 months for designs) prior to this United States application and of which I claim foreign priority benefits under Title 35, United States Code, Sec. 119, and I have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed.

EARLIEST FOREIGN APPLICATION, AND ALL FOREIGN APPLICATIONS FILED MORE THAN 12 MONTHS (6 MONTHS FOR DESIGN) PRIOR TO THIS U.S. APPLICATION

<u>Country</u>	<u>Application No.</u>	<u>Date of Filing</u> (month/day/year)
<u>United Kingdom</u>	<u>9824927.9</u>	<u>11/14/1998</u>
_____	_____	_____
_____	_____	_____



As a named inventor, I hereby appoint the practitioners associated with **Customer Number 007812** (John Smith-Hill, Reg. No. 27,730 and Daniel J. Bedell, Reg. No. 30,156) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith and in connection with the resulting patent.

Send correspondence to the correspondence address associated with **Customer Number 007812.**

I hereby authorize the practitioners that I have appointed to accept instructions regarding this application and the resulting patent from SWINDELL & PEARSON.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both under Title 18, United States Code, Sec. 1001, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first joint inventor _____

1-00 David Colley

Inventor's signature _____

Date 30th May 2001 Country of Citizenship Great Britain

Residence West Midlands, United Kingdom GBN

Post Office Address 119 Mill Road, Pelsall

Walsall, West Midlands WS4 1BU, United Kingdom

Full name of second joint inventor, if any _____

Inventor's signature _____

Date _____ Country of Citizenship _____

Residence _____

Post Office Address _____

FILED IN 66142800